

## Extreme Epoxy



### All Season Exterior Adhesive

A two-component exterior grade structural epoxy adhesive which cures at below freezing temperatures

- **PERMANENT** bonding
- Retaining Wall Capping
- Brick
- Concrete
- Stone
- Timber

Available in 50 ml, 250 ml and 600 ml cartridges, quarts, gallons and pails

## Duropoxi



### All Purpose Exterior Adhesive

A two component 1:1 ratio, water cleanable, epoxy adhesive

- Anchoring
- Extended Open Time
- **PERMANENT** bonding
- Retaining Wall Capping
- Brick
- Concrete
- Stone
- Timber

Available in quarts and gallons

## Other Applications



## Last Patch Limestone



### UV Stable Repair Product for Course Grained Stone and Concrete

An exterior grade stone repair compound designed for additional stone aggregate

- Cosmetic Repair Product
- Concrete Spall Repair
- Limestone
- Sandstone

Available in quarts

## Last Patch Gel



### UV Stable Repair Product for Fine Grained Stone

A UV stable aesthetic patch that can withstand sun exposure without discoloring

- For indoor & outdoor use
- Cosmetic Repair Product
- Stone Steps
- Granite
- Marble
- Travertine

Available in quarts



Above photos courtesy of Bennett Brothers Stone Co. Hot Springs, AR web: [bennettbrothersstone.com](http://bennettbrothersstone.com)

## Product Data Chart

### Product Name Color Consistency

Product Name	Color	Consistency	Mix ratio	Set-up time	Exterior	Interior	Horizontal applications	Vertical applications	Limestone / Travertine	Granite/ Marble	Patching	600ml cartridges	50ml cartridges	250ml cartridges	Quarts / or gallons	5 gallon pails
Fast Set™ Extreme	Buff	Non-sag	1 : 1	15 min	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Duropoxi™	Beige	Knife Grade	1 : 1	6 hr	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Last Patch Gel™	Clear	Knife Grade	1 : 1	15 min*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Last Patch Limestone™	Buff	Knife Grade	7 : 1	15 min*	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

For set times and full cure times under various temperatures, refer to product data sheets

\* When used with accelerator/Without accelerator 45 minutes

Note: When bonding limestone with aesthetic joints, use colored epoxy. Also tinting is recommended when patching with Last Patch Gel for porous stone.



**Bonstone Materials Corporation**

707 Swan Drive

Mukwonago, WI 53149

800-425-2214

tel 262-363-9877 fax 262-363-9879

www.bonstone.com info@bonstone.com

# ADHESIVES

**Proven Commercial  
Adhesives for the  
Hardscape Industry**

