



PRODUCT SPECIFICATIONS



PRODUCT NAME
ABR® Rubber Mask

MANUFACTURER
American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Rubber Mask is a temporary, removable latex coating designed to protect surfaces from paint overspray, tuckpointing smears and cleaning detergents.

Rubber Mask may be used on interior and exterior surfaces of painted or bare metal, masonite, OSB, brick, textured stone, concrete and plastic.

As a cleaner, **Rubber Mask** removes imbedded dirt particles and pollution residue when peeled from the surface it has been applied to.

The creamy consistency and opaque color of **Rubber Mask** allows for an even and “easy to see” application.

TECHNICAL DATA

Color/Form: cream colored paste
Coverage: 100-150 sq. ft. per gallon at 4 mils dry.
Storage Requirements: 50°-100°F

Rubber Mask freezes at 32°F. If Rubber Mask freezes it will no longer be usable.

Packaging: quart, one, and five gallon containers.



PROTECT FROM FREEZING

INSTALLATION

Limitations: **Rubber Mask** should not be applied when the air or surface temperature is below 50°F, or if rain or heavy moisture is forecasted.

Do not use on carpeting or fabric.

Do not use on unpainted or stained wood as discoloration may occur.

Preparatory Work: User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith. A test area should be processed prior to beginning the overall project to determine precise procedures necessary for most effective results and compatibility to surface being treated. Allow the test area to thoroughly dry then test the **Rubber Mask** for ease of removal and overall results.

APPLICATION

Surface must be dry and free of any dust, oil or foreign material.

1. Mix **Rubber Mask** well before use.
2. Apply at a temperature of 50°F or higher.
3. Apply a 1/8” thick wet coat (4 mils dry) to the surface with a brush, spatula or bulk caulking gun.
4. Allow the **Rubber Mask** to fully dry on the surface.
5. To remove the dried **Rubber Mask** start at a corner and peel the film away from the surface.
6. For extra protection to large areas, use with plastic sheeting: Due to its thick viscosity, **Rubber Mask** will hold plastic sheeting over an adjacent area. First, apply a single coat of **Rubber Mask**. Then, adhere the plastic sheeting to the **Rubber Mask** while it is still wet. In windy conditions, for

best results, apply a second coat of **Rubber Mask** over the outer edge of the plastic sheeting to better hold it in place.



A. Apply Rubber Mask to substrate



B. Apply plastic sheeting on top of Rubber Mask



C. Work on project – paint or stain



D. Remove Rubber Mask and plastic from substrate - no mess on adjacent surfaces





PRODUCT SPECIFICATIONS

Note: To ensure the ease of removal, remove **Rubber Mask** from the surface within 15 days of the initial date of application. **Do not apply** pure lacquers, alcohol, acetone, toluene or any solvent used in dissolving coatings over **Rubber Mask**.

Dry Time: Approximately 30 minutes to 2 hours, depending on temperature.

Clean Up: Water.

AVAILABILITY

Available through a network of distributors and dealers established in cities across the United States and Canada.

NOTICE: the information and recommendations made herein are based on ABRP, Inc., research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because ABRP, Inc., cannot anticipate every possible application of ABRP, Inc., products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of ABRP, Inc., products are not intended as recommendation to use ABRP, Inc., products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of product purchase. Purchaser's claims recovery is limited solely to the following warranty from ABRP, Inc., if the product herein is shown to be defective: ABRP, Inc., at its option, will either replace the product or refund the purchase price. Contact ABRP, Inc., to make claim under this warranty. The purchaser must have proof of purchase from the label and the original sales receipt. Proper surface preparation is essential to the product's performance and is a necessary prerequisite for triggering ABRP, Inc.'s obligation under this

warranty. Read and follow label directions and observe all safety precautions in the use of this product. ABRP, Inc., further disclaims, and shall not be liable for, incidental, consequential or indirect damage and/or personal injuries including death arising from the use of this product or the cost of labor involved in its application or any re-application of product that is replaced. SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS. NO OTHER WARRANTIES ARE MADE, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION WARRANTIES AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN ALL EVENTS, ABRP, INC.'S LIABILITY SHALL BE LIMITED SOLELY TO REPLACEMENT OF THE PRODUCT PROVIDED ABOVE. This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of ABRP, Inc., products. This warranty gives the purchaser specific legal rights, as well as rights which may vary from state to state. ABRP, Inc. specifically disclaims any and all other obligations or liability to any party relative to the sale, use or application of its products.

TECHNICAL SERVICES

ABRP, Inc., employs in-field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with ABRP, Inc., products and video training tapes demonstrating a variety of cleaning and restoration projects being performed with ABRP, Inc. products, are available upon specific request.

ABRP, INC., is on the WORLD WIDE WEB. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail ABRP, Inc. at abrp@abrp.com.

Copyright, 2009, American Building Restoration Products, Inc.

